

MICRO TOPPING

Extremely fine cement based trowel-able topping for a smooth thin set finish. Recommended for interior use only.

USES

As a thin set coloured overlay for concrete, masonry and fibrous cement surfaces. Micro Topping comes as a grey and a white cement base. By adding colour packs, to either base, the Micro Topping is excellent for colouring existing floors in residential and light commercial applications. Can be sanded within a couple of days to help achieve a smooth finish. Should always be sealed unless used as an underlayment. Excellent for skimming floors before chemical staining, especially when using a white base as the stains become more vibrant.

SURFACE PREPARATION

All surfaces must be clean and free from all loosely adhering particles and contaminants such as dirt, dust, oil, grease, etc, which effect bond. Any existing paints or coatings must be completely removed from surface to be coated. For new surfaces acid wash or grind for increased adhesion.

MIXING

Slowly add powder to 4.6litres of activator mix (1 part activator to 1 part water). If using colour, add colour to activator mix first. 1 x 400grm sachet per 10kg bag. Stir continuously with electrical mixer at a slow speed until smooth lump free consistency has been achieved. Let stand for 4 minutes and remix for 1 minute.

APPLICATION

Trowel down quickly and evenly across surface, in very warm conditions dampen surface down to prevent rapid water evaporation. For very porous surfaces, prime with a mixture of 1 part activator to 2 parts water. Spray or squeegee the primer, do not broom. Permacolour Flow Additive may also be added to increase flow and retarding effect. Priming the surface will always give more time to work the Micro Topping.

PRODUCT DATA

Form Cement based and fine aggregate powders
Part A of Part A & B.

Colour White & Grey

Application Temperature 5° to 30°C

Coverage 20m² at 0.5mm per 10kgs. This coverage depends on the experience of the contractor to trowel thin and evenly. Best allow for extra product when ordering.

Packaging 10kg bags

Note Part B is Permacolour Activator